



## AGRÖ10 RADIAL TRACTOR



COMFORTABLE DRIVE DUE TO FLEXIBLE  
SIDEWALL STRUCTURE

MUD REPELLENT FEATURE DUE TO SPECIALLY  
DESIGNED TREAD PATTERN

HIGH PERFORMANCE DUE TO DEEP TREADS AND  
WIDE BASE TRACK

### 65 Series

Code	Tyre Size	PR	Tubeless Tube Type	Rim ( Permitted )	Inflated Unloaded Dimensions		Load Index	Speed Index	Load and Pressure	
					Section Width (mm)	Overall Diameter (mm)			Tyre Load Capacity (kg)	Tyre Pressure (Psi)
R6524440	440/65R24	TL	W14L*24	W13*24,W15L*24	445	1185	128/131	D/A8	1800/1950	35
R6524480	480/65R24	TL	W15L*24	W14L*24	480	1235	133/136	D/A8	2060/2240	35
R6524540	540/65R24	TL			550	1320	146/149	D/A8	3000/3250	34
R6526750	750/65R26	TL	DW25B*26	DW23B*26,DW24B*26	755	1640	166/163	A8/B	5300/4875	34
R6528440	440/65R28	TL	W14L*28	W13*28,W15L*28	445	1285	131/134	D/A8	1950/2120	35
R6528480	480/65R28	TL	W15L*28	W14L*28	480	1337	142/145	D/A8	2650/2900	35
R6528540	540/65R28	TL	W16L*28	W18L*28	550	1420	149/152	D/A8	3250/3550	35
R6530540	540/65R30	TL			550	1470	150/153	D/A8	3350/3650	34
R6532800	800/65R32	TL	DW27B*32	DW25B*32,DH27B*32	800	1858	178/175	A8/B	7500/6900	46
R6534540	540/65R34	TL			550	1575	152/155	D/A8	3550/3875	34
R6538540	540/65R38	TL			550	1675	153/156	D/A8	3650/4000	34
R6538600	600/65R38	TL	DW20B*38	W18L*38	595	1750	159/162	D/A8	4375/4750	35
R6538650	650/65R38	TL	DW20B*38		650	1820	163/166	D/A8	4875/5300	34

### 70 Series

Code	Tyre Size	PR	Tubeless Tube Type	Rim ( Permitted )	Inflated Unloaded Dimensions		Load Index	Speed Index	Load and Pressure	
					Section Width (mm)	Overall Diameter (mm)			Tyre Load Capacity (kg)	Tyre Pressure (Psi)
R7016240	240/70R16	TL	W8*16	W8L*16, W9*16	245	745	104/104	A8/B	900/900	34
R7016260	260/70R16	TL	W8*16	W8L*16,W9*16	260	770	109/109	A8/B	1030/1030	34
R7016280	280/70R16	TL	W9*16	W8*16, W10*16	282	798	112/112	A8/B	1120/1120	34
R7018280	280/70R18	TL	W9*18	W8*18,W10*18	282	849	114/114	A8/B	1180/1180	34
R7020260	260/70R20	TL	W8*20	W8L*20,W9*20	260	875	113/113	A8/B	1150/1150	34
R7020280	280/70R20	TL	W9*20	W8*20, W10*20	282	900	116/116	A8/B	1250/1250	34
R7020300	300/70R20	TL	W9*20	W10*20	295	952	120/117	A8/B	1400/1285	34
R7020320	320/70R20	TL	W10*20	W9*20, W11*20	319	982	113/113	A8/B	1150/1150	23
R7020360	360/70R20	TL	W11*20	W10*20,W12*20	357	1042	129/129	A8/B	1850/1850	34
R7024320	320/70R24	TL	W10*24	W9*24, W11*24	319	1095	116/116	A8/B	1250/1250	23
R7024360	360/70R24	TL	W11*24	W10*24,W12*24	357	1152	122/122	A8/B	1500/1500	23
R7024380	380/70R24	TL	W12*24	W11*24,W13*24	380	1190	125/125	A8/B	1650/1650	23
R7024420	420/70R24	TL	W12*24	W13*24,W14L*24	418	1248	130/130	A8/B	1900/1900	23
R7024460	460/70R24	TL	W14*24	W15L*24,W16*24	460	1260	152/149	A8/B	3550/3250	23



INTRODUCTION FILM

Http Error Page  
Error Message:

Return to the [Default Page](#)