



## IND 80 TYRES FOR INDUSTRIAL OTR



HIGH TRACTION AND EXCELLENT SELF-CLEANING FEATURE IN ANY CONDITIONS THANKS TO DEEP AND CORRUGATED TREAD STRUCTURE

RESISTANT AGAINST STONE CUTS, CRACKS AND BREAKS,

HIGHER WEAR AND ROOT RESISTANCE THANKS TO USING BAR IN THE CENTER

RESISTANT TO ANY KIND OF IMPACTS

LONG WEAR-LIFE,

Code	Tyre Size	PR	Tubeless Tube Type	Rim ( Permitted )	Inflated Unloaded Dimensions		Load and Pressure			
					Section Width (mm)	Overall Diameter (mm)	Load Index	Speed Index	Tyre Load Capacity (kg)	Tyre Pressure (Psi)
6055	10-16.5	12	TUBELESS	8,25	256	793	138	A3	2360	84
6075	12-16.5	12	TUBELESS	9,75	297	858	144	A3	2800	83
6115	10.5/80-18	12	TUBELESS	W9	271	892	135	A8	2180	62
6156	12.5/80-18	14	TUBELESS	W9	285	955	146	A8	3000	62
6277	16.0/70-20	16	TUBELESS	13 SDC	385	1091	166	A2	5300	65
6286	15.5/80-24	14	TUBELESS	W12,W13	412	1269	144	A8	2800	51
6287	15.5/80-24	16	TUBELESS	W12,W13	412	1269	147	A8	3075	58
6377	16.0/70-24	16	TUBELESS	13 DC	418	1200	169	A2	5800	65
6396	16.9-24	14	TUBELESS	13 DC	429	1310	152	A8	3550	42
6516	18.4-26	14	TUBELESS	W15L	467	1425	160	A8	4500	42
6566	17.5L-24	14	TUBELESS	W 15L	475	1277	154	A8	3750	46
6616	16.9-28	14	TUBELESS	W15	429	1410	156	A8	4000	43
6816	15.5-25	14	TUBELESS	12,00/13i	400	1325	173	A2	6500	68
6957	16.9-30	16	TUBELESS	W15L	418	1466	156	A8	4000	47



Http Error Page  
Error Message:

[Return to the Default Page](#)