



## KNK 35 TRACTOR FRONT TYRE



TRACTOR FRONT TYRE CONFORM TO ASPHALT AND LAND USE

EXCELLENT MANEUVERABILITY AND NONDIRECTIONAL USE FEATURE THANKS TO ITS FLAT PATTERN

RESISTANT STRUCTURE AGAINST PUNCTURES THANKS TO INCREASED TREAD DEPTH

STRAIGHT MOVEMENT STABILITY IN SOFT LAND THANKS TO LINEAR PATTERN

Code	Tyre Size	PR	Tubeless Tube Type	Rim ( Permitted )	Inflated Unloaded Dimensions			Load and Pressure			
					Section Width (mm)	Overall Diameter (mm)	Load Index	Speed Index	Tyre Load Capacity (kg)	Tyre Pressure (Psi)	
3052	5.50-16	6	TUBE TYPE	4,00E	150	710	86	A6	530	54	
3053	5.50-16	8	TUBE TYPE	4,00E	150	710	91	A6	615	54	
3112	6.00-16	6	TUBE TYPE	4,50E	165	735	88	A6	560	48	
3113	6.00-16	8	TUBE TYPE	4,50E	165	735	93	A6	650	48	
3212	6.50-16	6	TUBE TYPE	4,50E	175	760	91	A6	615	45	
3213	6.50-16	8	TUBE TYPE	4,50E	175	760	97	A6	730	54	
3432	7.50-16	6	TUBE TYPE	5,50F	205	805	98	A6	750	41	
3433	7.50-16	8	TUBE TYPE	5,50F	205	805	103	A6	875	54	
3463	9.00-16	8	TUBE TYPE	W8	234	855	111	A6	1090	45	
3483	10.00-16	8	TUBE TYPE	W8	274	895	115	A6	1215	41	
3493	11.00-16	8	TUBE TYPE	10	315	965	118	A6	1320	36	
3502	7.50-18	6	TUBE TYPE	5,50F	205	860	101	A6	825	41	
3503	7.50-18	8	TUBE TYPE	5,50F	205	860	106	A6	950	54	



Http Error Page  
Error Message:

Return to the [Default Page](#)