



KNK 48 HARVESTER TYRE



HIGHWAY, AGRICULTURE AND OFFROAD TYRE
WITH HIGH LOAD BEARING CAPACITY AND LOW
SECTION

MINIMUM GROUND HOLDING FEATURE THANKS
TO WIDE CIRCUMFERENCE CHANNELS

MOVING FORWARD EASILY WITHOUT
SUBMERGING THANKS TO ITS WIDE TREAD
PATTERN

RESISTANT STRUCTURE AGAINST PUNCTURES
THANKS TO INCREASED TREAD DEPTH

| Code | Tyre Size | PR | Tubeless Tube Type | Rim (Permitted) | Inflated Unloaded Dimensions | | Load and Pressure | | | |
|------|------------|----|--------------------------|-------------------|------------------------------|-----------------------|-------------------|-------------|-------------------------|---------------------|
| | | | | | Section Width (mm) | Overall Diameter (mm) | Load Index | Speed Index | Tyre Load Capacity (kg) | Tyre Pressure (Psi) |
| 4605 | 10.5/80-18 | 12 | TUBE TYPE | 9 | 274 | 885 | 135 | A8 | 2180 | 65 |
| 4626 | 12.5/80-18 | 14 | TUBE TYPE | 9 | 308 | 965 | 144 | A8 | 2800 | 63 |
| 4647 | 13.0/65-18 | 16 | TUBE TYPE | 11 | 336 | 890 | 144 | A8 | 2800 | 66 |



Http Error Page
Error Message:

Return to the [Default Page](#)