



## KNK 70 TYRES FOR INDUSTRIAL OTR



ITS PERFECT DESIGN HAS STRONG RESISTANCE TO HEAT AND CORROSION, STRONG DESIGNED PATTERN CONSIST OF COMBINED BLOCKS

ITS COMPUND IS RESISTANT TO WEAR, AND ITS BLOCKS RESISTANT TO HEAVY CONDITIONS WITH LONG MAINTENANCE PERIODS,

MINIMIZES STRETCHING AT BASE WITH ITS STRONG BLOCKS IN ITS CENTER

Code	Tyre Size	PR	Tubeless Tube Type	Rim ( Permitted )	Inflated Unloaded Dimensions		Load and Pressure			
					Section Width (mm)	Overall Diameter (mm)	Load Index	Speed Index	Tyre Load Capacity (kg)	Tyre Pressure (Psi)
6761	14.00-24	24	TUBELESS	10,00 VA	375	1360	186	A2	9500	123
6765	14.00-24	32	TUBELESS	10,00 VA	375	1360	190	A2	10600	145
6419	17.5-25	20	TUBELESS	14,00/1,5	455	1371	181	A2	8250	83
6439	20.5-25	20	TUBELESS	17,00/2,0	531	1527	186	A2	9500	65
6431	20.5-25	24	TUBELESS	17,00/2,0	531	1527	189	A2	10300	76
6459	23.5-25	20	TUBELESS	19,50/2,5	604	1625	191	A2	10900	65
6451	23.5-25	24	TUBELESS	19,50/2,5	604	1625	196	A2	12500	68
6473	26.5-25	28	TUBELESS	22,00/3,0	702	1785	203	A2	15500	68
6475	26.5-25	32	TUBELESS	22,00/3,0	702	1785	206	A2	17000	79
6495	29.5-25	32	TUBELESS	25,00/3,5	758	1923	210	A2	19000	72
6525	18.00-25	32	TUBELESS	13,00/2,5	498	1615	183	B	8750	83
6529	18.00-25	40	TUBELESS	13,00/2,5	498	1615	206	A2	17000	138



Http Error Page  
Error Message:

[Return to the Default Page](#)