



KNK 77 TYRES FOR INDUSTRIAL OTR



WIDE SHOULDER AND BASE WIDTH, BLOCKED DESIGN

PROVIDES HIGH TRACTION ABILITY.

ANTI-WEAR FUTURE THANKS TO ITS PATTERN APPROPRIATE FOR AGRICULTURAL, INDUSTRIAL AND OFFROAD USE

CONSISTS OF DURABLE BLOCKS.

EASY USE IN SOFT GROUNDS, SUCH AS SAND AND ROADWORK

WIDE SHOULDER AND BLOCKS PROVIDE BALANCED DRIVING AND EASY CONTROL

Code	Tyre Size	PR	Tubeless Tube Type	Rim (Permitted)	Inflated Unloaded Dimensions			Load and Pressure		
					Section Width (mm)	Overall Diameter (mm)	Load Index	Speed Index	Tyre Load Capacity (kg)	Tyre Pressure (Psi)
6534	23.1-26	10	TUBELESS	DW20	587	1580	158	A8	4250	25
6535	23.1-26	12	TUBELESS	DW20	587	1580	162	A8	4750	28
6536	23.1-26	14	TUBELESS	DW20	587	1580	166	A8	5300	33



Http Error Page
Error Message:

[Return to the Default Page](#)